



Up to 17.2 SEER2 and 8.2 HSPF2



## High-Efficiency, Communicating, Split System Heat Pump

## Contents

Nomenclature	2
Product Specifications	3
Expanded Cooling Data	4
Expanded Heating Data	20
Wiring Diagram	
Dimensions	23
Accessories	23



.

•



## **Standard Features**

- Two-Stage Copeland<sup>®</sup> UltraTech scroll compressor
- High-density foam compressor sound blanket
- Integrated communicating ComfortBridge<sup>™</sup> technology
- Commissioning and diagnostics via indoor board Bluetooth with the CoolCloud™ phone and tablet application
- ComfortAlert<sup>™</sup> built in diagnostics
- Copper tube/enhanced aluminum fin coil- 5mm on 2.0-3.0T
- Efficient, two-speed ECM condenser fan motor
- Simple low-voltage wiring to outdoor unit in communicating mode
- Diagnostic indicator lights and storage of six fault codes
- Color-coded terminal strip for non-communicating set-up
- High- and low-pressure switches
- Time-delay technology with short-cycle protection to ensure quiet, reliable defrost
- Factory-installed bi-flow liquid-line filter drier
- Factory-installed suction-line accumulator
- Factory-installed compressor crankcase heater
- Factory-installed high-capacity muffler
- Factory-installed coil and ambient temperature sensors
- AHRI Certified; ETL Listed



UNIT

LIMITED

YEAR





Most Efficient

2023



Products that are recognized as the Most Efficient of ENERGY STAR® in 2023

prevent greenhouse gas emissions by meeting rigorousenergy efficiency

\* Proper sizing and installation of equipment is critical to achieve optimal

performance. Split system air conditioners and heat pumps must be matchedwith apprpriate coil components to meet

ENERGY STAR criteria. Ask your contractor for details or

performance levels set by the U.S. Environmental Protection Agency.

waCcambledetails available from your local dealer or at www.goodmanmfg.com. To receive the Lifetime Compressor Limited Warranty (good for as long as you own your home), 10-Year Compressor Replacement Limited Warranty and 10-Year Parts Limited Warranty, online registration in such the completed within 60 days of installation. Online registration is not required in California or Québec.

**Cabinet Features** 

Grille-style sound control top design

500-hour salt-spray tested

Single panel access to controls

Sweat connection service valves with easy access to gauge ports

Wire fan discharge grille

Steel louver coil guard

Custom Nickel Gray powder-paint finish

with space provided for field-installed accessories

When properly anchored, meets the 2020 Florida

hurricane-type winds (Anchor bracket kits available.)

visit www.energystar.gov.

Building Code unit integrity requirements for

